



**CVS speed sensor mounting bracket**  
 Cut, fold and drill this bracket as required to mount the inductive speed sensor in a position suitable to be triggered by the speed sensor target.




**CVS speed sensor target bracket**  
 Cut, fold and drill this bracket as required to mount to the end of a rotating shaft on the conveyer belt so that the steel capscrew will trigger the inductive speed sensor once per revolution.



**CVS speed sensor alignment**  
 Mount the speed sensor and target so the target will be between 3mm and 5mm from the sensor when it travels past. Make sure the target passes as close as possible through the centre of the speed sensor.

DO NOT SCALE Dimensions in mm	 3rd Angle PROJECTION	Drawn by: <b>Brad Webb</b>	Description: CVS Speed Sensor Installation	Revision:	Drawing Scale: <b>1:2</b>	<a href="http://www.LOADCAN.com">www.LOADCAN.com</a>  LOAD VOLUME SCANNER				
		Drawn Date: <b>8/11/2018</b>					Drawing Number: <b>CVS</b>	<b>A</b>	Sheet: <b>1 of 5</b>	105 Higgins Road, Dinsdale, Hamilton, New Zealand Tel: +64 7 847 5777 Fax: +64 7 847 4807
		Approved by:								




**Example 1:** Both brackets have been cut short and drilled for mounting. The target bracket has then been folded so that the end of the capscrew will pass across the inductive speed sensor once per revolution of the conveyer drive roller

DO NOT SCALE Dimensions in mm	 3rd Angle PROJECTION	Drawn by: <b>Brad Webb</b>	Description: CVS Speed Sensor Installation	Revision:	Drawing Scale: <b>1:2</b>	<a href="http://www.LOADSCAN.com">www.LOADSCAN.com</a>  LOAD VOLUME SCANNER 105 Higgins Road, Dinsdale, Hamilton, New Zealand Tel: +64 7 847 5777 Fax: +64 7 847 4807
		Drawn Date: <b>8/11/2018</b>				
		Approved by:				

10 9 8 7 6 5 4 3 2 1

H  
G  
F  
E  
D  
C  
B



**Example 2:** Both brackets have been cut short and drilled for mounting. The sensor mounting bracket has then been folded so that the side of the capscrew will pass across the inductive speed sensor once per revolution of the conveyor drive roller.

H  
G  
F  
E  
D  
C  
B

DO NOT SCALE Dimensions in mm	 3rd Angle PROJECTION	Drawn by: <b>Brad Webb</b>	Description: CVS Speed Sensor Installation	Revision:	Drawing Scale: <b>1:2</b>	<a href="http://www.LOADSCAN.com">www.LOADSCAN.com</a>  LOAD VOLUME SCANNER				
		Drawn Date: <b>8/11/2018</b>					Drawing Number: <b>CVS</b>	<div style="font-size: 2em; font-weight: bold; text-align: center;">A</div>	Sheet: <b>3 of 5</b>	105 Higgins Road, Dinsdale, Hamilton, New Zealand Tel: +64 7 847 5777 Fax: +64 7 847 4807
		Approved by:								


10 9 8 7 6 5 4 3 2 1

A

A

10 9 8 7 6 5 4 3 2 1

H  
G  
F  
E  
D  
C  
B



**Example 3:** Both brackets have been cut short and drilled for mounting. Both have then been folded so that the end of the capscrew will pass across the inductive speed sensor once per revolution of the conveyer drive roller.


H  
G  
F  
E  
D  
C  
B

DO NOT SCALE Dimensions in mm	 3rd Angle PROJECTION	Drawn by: <b>Brad Webb</b>	Description: CVS Speed Sensor Installation	Revision:	Drawing Scale: <b>1:2</b>	<a href="http://www.LOADSCAN.com">www.LOADSCAN.com</a>  LOAD VOLUME SCANNER
		Drawn Date: <b>8/11/2018</b>				
		Approved by:	105 Higgins Road, Dinsdale, Hamilton, New Zealand Tel: +64 7 847 5777 Fax: +64 7 847 4807			

10 9 8 7 6 5 4 3 2 1

A

A



**Example 4:** The sensor mounting bracket has been cut short and drilled for mounting. The target bracket is not used in this case and instead a bolt had been tapped into the side of the drive roller so that it passes across the inductive speed sensor once per revolution of the conveyer drive roller.

DO NOT SCALE Dimensions in mm	 3rd Angle PROJECTION	Drawn by: <b>Brad Webb</b>	Description: CVS Speed Sensor Installation  Drawing Number: <b>CVS</b>	Revision:  <b>A</b>	Drawing Scale: <b>1:2</b>	www.LOADSCAN.com  LOAD VOLUME SCANNER 105 Higgins Road, Dinsdale, Hamilton, New Zealand Tel: +64 7 847 5777 Fax: +64 7 847 4807
		Drawn Date: <b>8/11/2018</b>			Sheet: <b>5 of 5</b>	
		Approved by:				